

CAMPANE CARRELLATE
STANDING CHAMBERS
CAMPANAS SOBRERUEDAS

DISPONIBILI DA MAGGIO 2021
AVAILABLE FROM MAY 2021
DISPONIBLE A PARTIR DE MAYO 2021

INDUSTRIAL

20 PROGRAMMI
PROGRAMS
PROGRAMAS

- SOFT VACUUM
- MARINATING FUNCTION
- VACUUM SENSOR



BLIZZARD

ALYSEE

TORNADO

| | | | |
|---|--|--|--|
| Dimensioni macchina Machine dimensions Dimensiones máquina | 700x750x1110 h mm | 780x750x1110 h mm | 890x750x1110 h mm |
| Peso / Weight / Peso | 100 kg ^A 119 kg ^B | 191 kg ^A 215 kg ^B | 220 kg ^A 227 kg ^B |
| Voltaggio / Voltage / Voltaje | 110 V-50/60 Hz ^A ● 230 V-50/60 Hz ^A ● 220 V-50/60 Hz 3ph ^B ● 380 V-50/60 Hz 3ph ^B ● | 220 V-50/60 Hz 3ph ● 380 V-50/60 Hz 3ph | 220 V-50/60 Hz 3ph ● 380 V-50/60 Hz 3ph |
| Consumo / Consumption / Consumo | 0,9 ^A 1,6 ^B kW ● | 1,6 ^A 1,8 ^B kW | 1,8 ^A 2,35 ^B kW |
| Dimensioni camera Chamber dimensions Dimensiones cámara | 530x530x200 mm | 660x540x250 mm | 760x540x250 mm |
| Pompa a bagno d'olio Oil lubricated pump Bomba de baño de aceite | 25 m3/h Busch® ^A 40 m3/h Becker® ^B | 40 m3/h Becker® ^A 71 m3/h Becker® ^B | 71 m3/h Becker® ^A 101 m3/h Becker® ^B |
| Barra saldante Welding bar Barra de soldadura | ☐ 520 mm ● ☐ 520/520 mm | ☐ 650/650 mm ● ☐ 520/520 mm ☐ 520/580 mm ● ☐ 520/515/520 mm | ☐ 750/750 mm ● ☐ 520/520 mm ☐ 520/680 mm ● ☐ 520/615/520 mm |
| Seconda barra saldante (opz.) Second welding bar (opt.) Segunda barra de soldadura (opc.) | ✓ | × | × |
| Terza barra saldante (opz.) Third welding bar (opt.) Tercera barra de soldadura (opc.) | × | ✓ | ✓ |
| Barra taglio sfrido (opz.) ● Cut-off seal bar (opt.) Barra con corte de bolsa (opc.) | ✓ | ✓ | ✓ |
| Barra doppia saldatura (opz.) ● Double seal bar (opt.) Barra doble soldadura (opc.) | ✓ | ✓ | ✓ |
| Atmosfera protettiva (opz.) Protective atmosphere (opt.) Atmósfera protegida (opc.) | ✓ | ✓ | ✓ |
| Sensore di vuoto (opz.) ● Vacuum sensor (opt.) Sensor de vacío (opc.) | Incluso Included Incluido | Incluso Included Incluido | Incluso Included Incluido |
| Funzione marinatura (opz.) ● Marinating function (opt.) Funcion marinado (opc.) | Incluso Included Incluido | Incluso Included Incluido | Incluso Included Incluido |
| Stampante (opz.) Printer (opt.) Impresora (opc.) | ✓ | ✓ | ✓ |
| Soft air (opz.) Soft air (opt.) Soft air (opc.) | ✓ | ✓ | ✓ |
| Predisposizione vuoto teglie GN (opz.) Vacuum in GN pans prearrangement (opt.) Predisposición vacío en bandejas GN (opc.) | Incluso Included Incluido | ✓ | ✓ |
| Piano inclinato per liquidi (acc.) Liquids inclined shelf (acc.) Estante inclinado para líquidos (acc.) | ✓ | Su richiesta On demand Bajo pedido | Su richiesta On demand Bajo pedido |

● Voltaggio speciale prezzo su richiesta

● Opzioni non cumulabili

● Di serie

Special voltage price on demand

Non-cumulative options

Standard

Voltaje especial precio a petición

Opciones no acumulativas

Estándar

DISPONIBILI DA MAGGIO 2021
AVAILABLE FROM MAY 2021
DISPONIBLE A PARTIR DE MAYO 2021

INDUSTRIAL

20 PROGRAMMI
PROGRAMS
PROGRÁMAS

- SOFT VACUUM
- MARINATING FUNCTION
- VACUUM SENSOR



MONSOON

MONSOON MT

MEAT INDUSTRY

LESTE

| | | | |
|---|--|--|---|
| Dimensioni macchina Machine dimensions Dimensiones máquina | 1090x750x1110 h mm | 1090x750x1110 h mm | 1250x900x1100 h mm |
| Peso / Weight / Peso | 252 kg | 289 kg | 297 kg |
| Voltaggio / Voltage / Voltaje | 220 V-50/60 Hz 3ph ● 380 V-50/60 Hz 3ph | 220 V-50/60 Hz 3ph ● 380 V-50/60 Hz 3ph | 220 V-50/60 Hz 3ph ● 380 V-50/60 Hz 3ph |
| Consumo / Consumption / Consumo | 2,50 kW | 2,50 kW | 2,20 kW |
| Dimensioni camera Chamber dimensions Dimensiones cámara | 960x540x250 mm | 960x540x250 mm | 1100x620x290 h mm |
| Pompa a bagno d'olio Oil lubricated pump Bomba de baño de aceite | 101 m3/h Becker® | 166 m3/h Becker® | 166 m3/h Becker® |
| Barra saldante Welding bar Barra de soldadura | <input type="checkbox"/> 950/950 mm ● <input type="checkbox"/> 520/520 mm <input type="checkbox"/> 520/880 mm ● <input type="checkbox"/> 520/815/520 mm | <input type="checkbox"/> 950/950 mm ● <input type="checkbox"/> 520/520 mm <input type="checkbox"/> 520/880 mm ● <input type="checkbox"/> 520/815/520 mm | <input type="checkbox"/> 1090/1090 mm ● <input type="checkbox"/> 605/605 mm <input type="checkbox"/> 605/1035 mm ● <input type="checkbox"/> 605/990/605 mm |
| Terza barra saldante (opz.) Third welding bar (opt.) Tercera barra de soldadura (opc.) | ✓ | ✓ | ✓ |
| Barra taglio sfrido (opz.) ● Cut-off seal bar (opt.) Barra con corte de bolsa (opc.) | ✓ | ✓ | ✓ |
| Barra doppia saldatura (opz.) ● Double seal bar (opt.) Barra doble soldadura (opc.) | ✓ | ✓ | ✓ |
| Atmosfera protettiva (opz.) Protective atmosphere (opt.) Atmósfera protegida (opc.) | ✓ | ✓ | ✓ |
| Sensore di vuoto (opz.) ● Vacuum sensor (opt.) Sensor de vacío (opc.) | Incluso Included Incluido | Incluso Included Incluido | Incluso Included Incluido |
| Funzione marinatura (opz.) ● Marinating function (opt.) Funcion marinado (opc.) | Incluso Included Incluido | Incluso Included Incluido | Incluso Included Incluido |
| Stampante (opz.) Printer (opt.) Impresora (opc.) | ✓ | ✓ | ✓ |
| Soft air (opz.) Soft air (opt.) Soft air (opc.) | ✓ | ✓ | ✓ |
| Predisposizione vuoto teglie GN (opz.) Vacuum in GN pans prearrangement (opt.) Predisposición vacío en bandejas GN (opc.) | ✓ | ✓ | ✓ |
| Piano inclinato per liquidi (acc.) Liquids inclined shelf (acc.) Estante inclinado para líquidos (acc.) | Su richiesta On demand Bajo pedido | Su richiesta On demand Bajo pedido | Su richiesta On demand Bajo pedido |

● Extra vuoto

● Selezionare solo 1 barra per taglio sfrido

A Prezzo pompa 1; B prezzo pompa 2

Extra vacuum

Select just 1 bar for cut-off seal bar

A Pump price 1; B Pump price 2

Extra vacío

Seleccionar 1 sola barra para corte al ras

A Precio bomba 1; B Precio bomba 2