



CAMPANE INDUSTRIALI CARRELLATE
INDUSTRIAL FLOOR MODELS
CAMPANAS DE SOBREMESA
MODÈLES SUR SOCLE INDUSTRIELS
INDUSTRIELLE STANDMODELLE

INDUSTRIAL
Sliding

20 PROGRAMMI
PROGRAMS
PROGRAMAS
PROGRAMMES
PROGRAMME

- SOFT VACUUM
- MARINATING FUNCTION
- VACUUM SENSOR



STORM




CYCLON



BAYAMO



TYPHOON



HURRICANE

Dimensioni macchina

Machine dimensions

Dimensiones máquina

Dimensions de la machine

Maschinenabmessungen

1060 x 900 x
1179h mm

1260 x 1020 x
1185h mm

1483 x 1204 x
1341h mm

1900 x 1295 x
1450h mm

2420 x 1213 x
1597h mm

Peso | Weight | Peso | Poids |
Gewicht

236 Kg

319 Kg

537 Kg

685 Kg

767 Kg

Voltaggio | Voltage | Voltaje | Tension
| Spannung

400 V-3-50 Hz
220 V-3-60 Hz ●

400 V-3-50 Hz
220 V-3-60 Hz ●

400V-3-50 Hz
220V-3-60 Hz ●

400V-3-50 Hz
220V-3-60 Hz ●

400V-3-50Hz
220V-3-60Hz ●

Consumo | Consumption | Consumo |
Consommation | Leistung

2,4 - 3,5 kW

3,0 - 5,0 kW

5,5 - 9,0 kW

7,0 - 9,0 kW

7,0 - 9,0 kW

Dimensioni camera | Chamber
dimensions | Dimensiones

cámara | Dimensions de la cuve |

Kammergröße

(2x)
580x450x235 mm

(2x)
700x550x235 mm

(2x)
750x620x250 h mm

(2x)
830x840x255 h mm

(2x)
730x1100x280 h mm*
1000x850x280 h mm**

Pompa a bagno d'olio | Oil
lubricated pump | Bomba de baño
de aceite | Pompe à bain d'huile |
Ölvakumpumpe

63 m3/h Busch®

100 m3/h Busch®

160 m3/h Busch®

300 m3/h Busch®

300 m3/h Busch®

Barra saldante | Welding bar | Barra
de soldadura | Barre de soudure |
Schweißbalken

(2x)
☐ 450/450 mm ●
☐ 680/680 mm

(2x)
☐ 550/550 mm ●

(2x)
☐ 620/620 mm ●
☐ 840/840 mm

(2x)
☐ 840/840 mm ●
☐ 770/770 mm

(2x)
☐ 1100/1100 mm* ●
☐ 850/850 mm**

Barra taglio sfrido (opz.) ●

Cut-off seal bar (opt.)

Barra con corte de bolsa (opc.)

Barre soudure coupure (opt.)

Schweißbalken mit Abscheider (opt.)

●

●

●

●

●

Barra doppia saldatura ●

Double seal bar

Barra doble soldadura

Barre double soudure

Doppelschweißbalken

●

●

●

●

●

Atmosfera protettiva (opz.)

Protective atmosphere (opt.)

Atmósfera protegida (opc.)

Atmosphère modifiée (opt.)

Schutzatmosphäre (opt.)

●

●

●

●

●

● Prezzi disponibili su richiesta

Prices available on request

Precios disponibles bajo petición

Prix disponibles sur demande

Auf Anfrage erhältliche Preise

● Voltaggio speciale prezzo su richiesta

Special voltage price on demand

Voltaje especial precio a petición

Tension spéciale sur demande

Spezielle Spannung auf Anfrage

● Extra vuoto

Extra vacuum

Extra vacío

Vide supplémentaire

Extravakuum

● Opzioni non cumulabili

Non-cumulative options

Opciones no acumulativas

Options non cumulables

Nicht kombinierbare Optionen

● Di serie

Standard

Estándar

De série

Standard



CAMPANE INDUSTRIALI CARRELLATE
 INDUSTRIAL FLOOR MODELS
 CAMPANAS DE SOBREMESA
 MODÈLES SUR SOCLE INDUSTRIELS
 INDUSTRIELLE STANDMODELLE

INDUSTRIAL
 Sliding

20 PROGRAMMI
 PROGRAMS
 PROGRAMAS
 PROGRAMMES
 PROGRAMME

- SOFT VACUUM
 - MARINATING FUNCTION
 - VACUUM SENSOR



Sensore di vuoto ● Vacuum sensor Sensor de vacío Capteur de vide Vakuumsensor	●	●	●	●	●
Funzione marinatura ● Marinating function Funcion de marinado Fonction de marinade Marinierfunktion	●	●	●	●	●
Stampante (opz.) Printer (opt.) Impresora (opc.) Imprimante (opt.) Drucker (opt.)	●	●	●	●	●
Terza barra saldante (opz.) Third welding bar (opt.) Tercera barra de soldadura (opc.) Troisième barre de soudure (opt.) Dritter Schweißbalken (opt.)	×	×	×	×	Su richiesta On demand Bajo pedido Sur demande Auf Anfrage