



CYCLON

Dimensioni macchina Machine dimensions Dimensiones máquina Dimensions de la machine Maschinenabmessungen	1260 x 1020 x 1185h mm	Barra taglio sfrido (opz.) ● Cut-off seal bar (opt.) Barra con corte de bolsa (opc.) ● Barre soudure coupure (opt.) Schweißbalken mit Abschneider (opt.)
Peso Weight Peso Poids Gewicht	319 Kg	Barra doppia saldatura ● Double seal bar Barra doble soldadura ● Barre double soudure Doppelschweißbalken
Voltaggio Voltage Voltaje Tension Spannung	400 V-3-50 Hz 220 V-3-60 Hz ●	Atmosfera protettiva (opz.) Protective atmosphere (opt.) Atmosfera protegida (opc.) ● Atmosphère modifiée (opt.) Schutzatmosphäre (opt.)
Consumo Consumption Consumo Consumation Leistung	3,0-5,0 kW	Sensore di vuoto ● Vacuum sensor Sensor de vacío ● Capteur de vide Vakuumsensor
Dimensioni camera Chamber dimensions Dimensiones cámara Dimensions de la cuve Kammergröße	(2x) 700x550x235 mm	Funzione marinatura ● Marinating function Funcion de marinado ● Fonction de marinade Marinierfunktion
Pompa a bagno d'olio Oil lubricated pump Bomba de baño de aceite Pompe à bain d'huile Ölvakuumpumpe	100 m3/h Becker®	Stampante (opz.) Printer (opt.) Impresora (opc.) ● Imprimante (opt.) Drucker (opt.)
Barra saldante Welding bar Barra de soldadura Barre de soudure Schweißbalken	(2x) ☐ 550/550 mm ●	Terza barra saldante (opz.) Third welding bar (opt.) Tercera barra de soldadura (opc.) Troisième barre de soudure (opt.) Dritter Schweißbalken (opt.) ×